

HeroEE 1

SOLAR GENERATOR

1004.8Wh

200W



Light

15W ≈ 56h



Fan

30W ≈ 28h



CCTV

40W ≈ 21h



Laptop

60W ≈ 14h



Ultra-Long Life



Installation-Free



Plug And Play



Maintenance-Free



PRODUCT DETAILS

Model	HeroEE 1
Battery Type	LiFePO ₄
Battery Capacity	1004.8Wh
Cell Capacity	314Ah
Battery Cycles	11000 cycles@(25°C , 100%DOD , 0.5P , @70%SOH)
AC Output Power	200W
AC Output Voltage	200~240[VAC]@typical value(Bypass Mode)/ 230[VAC]@typical value(Inverter Mode),50Hz@typical value
AC Input Power	200W
AC Input Voltage	200-240[VAC]@typical value,50Hz@typical value
Max. PV Input Power	200W
PV Input Voltage	12-36[VDC]
Max.PV Input Current	11A
Ingress Protection Level	IP20
Protection	AC Input Overvoltage/Undervoltage, AC Output Overvoltage/Overload/ Undervoltage/OverCurrent/Short Circuit, Battery Cell High/ Low Temperature/Overcurrent/Undervoltage/Short Circuit/ Ovecurrent, Over Temperature
Operating / Temperature	Charging: 0°C~40°C Discharging: -20°C~40°C
Storage Temperature	-20°C~60°C
Humidity	10%~90%
Net Weight	8.26kg
Dimensions	L210*W130*H285mm
Certification	CE、CB、UN38.3, IEC62619

*The above is for reference only, the specification sheet shall prevail.

Contact:

Tel:

<https://www.hero-ee.com>



Business Cooperation



website